

# Platinum aluminum wheelchair

catalogue number: VCWK9ASZ

## PRODUCT CHARACTERISTICS:

- foldable, aluminium frame,
- adjustable seat,
- safety belts,
- lifted footrests (removable and tilting to rear) with adjustable angle of foot platform,
- belt retaining calfs,
- brakes with pressure adjustment,
- rear wheels equipped with quick-release lock system,
- anti-tip wheels (height adjustable),
- anti-bedsore cushion,
- reflective elements,
- pocket in backrest upholstery,
- possibility of seat height adjust,
- modular construction,
- suitable for amputees,
- option of using special Varioblock,
- profiled handles for caretaker,
- possibility to adjust angle of the seat through customize height of wheels,
- aluminum spokes,
- adjustable angle of front wheels,
- ability to change the center of gravity by moving driving wheels backwards,
- attractive design,
- set widths: 16" / 17" / 18" / 20"
- pump included (for wheelchairs with pumped wheels),
- keys included,
- wheelchair colour: champagne, upholstery colour: black (possibility to remove the backrest of upholstery).


## USE:

General use wheelchair, at home and for strolls.



**VITEA<sup>®</sup>**  
**CARE**

Specifications (succesively sizes: 16", 17", 18", 20"):

<b>User maximum weight</b>	140 kilograms 			
<b>Product lasting</b>	5 years from production date			
<b>Wheelchair height</b>	950 mm			
<b>Seat width</b>	410 mm	430 mm	460 mm	500 mm
<b>Wheelchair width</b>	650 mm	670 mm	700 mm	740 mm
<b>Maximum lenght of wheelchair</b>	108 mm			
<b>Seat depth</b>	400 mm			
<b>Back width</b>	410 mm	430 mm	460 mm	500 mm
<b>Back lenght</b>	430 mm			
<b>Seat height</b>	470 mm			
<b>Wheelchair dimensions when folded</b>	350 x 950 x 800 mm			
<b>Wheelchair weight</b>	17 ± 5% kg			
<b>Wheelchair weight without additional components</b>	15 ± 5% kg			
<b>Minimal turning radius</b>	110°			
<b>Material</b>	Aluminum, polyurethane, rubber			
<b>Rear pumped wheels size equipped with quick-release lock system</b>	24", (diameter 610 mm)			
<b>Front wheels size</b>	8", ( diameter 200 mm)			